

| Cat Desc   | Qty |
|--|-----|
| ADAPTER, ABSOLUTE ENCODER MULTITURN, PROFIBUS, FITS ATM 60 ENCODER, RESOLUTION UP TO 26 BITS   | 1   |
| AIR CONDITIONER, 22000 BTU, 208-230VAC 1PH 60HZ, SELF CONTAINED, W/ 4KW HEATER   | 1   |
| ANEMOMETER, WIND SPEED TRANSMITTER, LESS THAN 2 KNOTS AND GREATER, DC MAGNET GENERATOR, BAKED ENAMEL COVERED BRASS HSG, WEATHERPROOF | 1   |
| BEARING, BALL, CONRAD, DEEP GROOVE, SINGLE ROW, 1.1811 IN ID, 2.4409 IN OD, 0.6299 IN WD, SHIELD                                     | 1   |
| BEARING, BALL, CONRAD, RADIAL, DEEP GROOVE, SINGLE ROW, 0.984 IN ID, 1.85 IN OD, 0.472 IN WD, C3, STEEL CAGE                         | 1   |
| BEARING, BALL, DEEP GROOVE, SINGLE ROW, 40MM ID, 80MM OD, 18MM WD, SEALED, STEEL CAGE  | 1   |
| BEARING, ROD END, SPHERICAL, LH THD, F/ BUCKET CYLINDER  | 1   |
| BEARING, ROD END, SPHERICAL, RH THD, F/ BUCKET CYLINDER  | 1   |
| BEARING, ROLLER, CYLINDRICAL, SINGLE ROW, 100MM ID, 180MM OD, 34MM WD, STEEL CAGE  | 1   |
| BEARING, ROLLER, NEEDLE, SINGLE ROW, 0.625 IN ID, 0.813 IN OD, 0.75 IN WD, STEEL CAGE  | 2   |
| BEARING, ROLLER, NEEDLE, SINGLE ROW, 0.688 IN ID, 0.875 IN OD, 0.75 IN WD, STEEL CAGE  | 1   |
| BEARING, ROLLER, SPHERICAL, TAPERED, DOUBLE ROW, 130MM ID, 210MM OD, 64MM WD, BRONZE CAGE, CYLINDRICAL BORE, UNSEALED                | 1   |
| BEARING, THRUST, 0.563 IN ID, 1.063 IN OD, BRONZE  | 1   |
| BRUSH, ELECTRICAL, ***, 2.5 IN BORE, COPPER GRAPHITE, 35AMP  | 1   |
| BRUSH, ELECTRICAL, ***, 2.5 IN BORE, SILVER GRAPHITE, 15AMP  | 1   |
| BUSHING, BARGE UNLOADER, 3.248 IN ID X 3.751 IN OD X 4-1/4 IN LG, CARBURIZE & HARDENED STEEL, 5 IN DIA FLANGE                        | 1   |
| BUSHING, BARGE UNLOADER, 4.998 IN ID X 5.501 IN OD X 4 IN LG, CARBURIZE & HARDENED STEEL   | 1   |
| BUSHING, BEARING, 10 IN ID X 11 IN OD X 6 IN HT, OIL LITE BRASS, RPM DWG MET 21902   | 1   |
| BUSHING, BEARING, 14-1/2 IN ID X 16 IN OD X 10 IN HT, OIL LITE BRASS, RPM DRAWING #MET 21901, SPARE LINE 1524 FGD                    | 1   |
| BUSHING, BEARING, 5.13 IN OD X 3.95 IN OD X 3.38 IN HT, OIL LITE BRASS, RPM DWG MET 21905  | 1   |
| CONNECTOR, COMMUNICATIONS, PLUG, 2 POLE  | 2   |
| CONTROLLER, JOYSTICK, -25 TO +70 DEG C TEMP RANGE, 240VAC, LH  | 1   |
| CONTROLLER, JOYSTICK, -25 TO +70 DEG C TEMP RANGE, 240VAC, RH  | 1   |
| DISC, BRAKE, LOAD, 3/4 IN ID X 2-7/8 IN OD, FIBER MATERIAL   | 2   |
| DISC, BRAKE, REDUCER, PKG QTY: 8 PCS/SET   | 1   |
| DRIVE, AC MOTOR, 6 HP, 3PH 480VAC 9AMP INPUT, 24VDC OUTPUT, NEMA 1/IP21 ENCLOSURE, 5 IN WD X 12.9 IN HT X 7-1/2 IN DP                | 1   |
| ELEMENT, FILTER, HYDRAULIC, 49.5MM ID X 85.5MM OD X 652MM LG, 25 MICRON, MICROGLASS FIBER/PLASTIC, NITRILE SEALS, 26 IN LG           | 4   |
| ENCODER, ROTARY OPTICAL ABSOLUTE, 10-32V, 13 BITS/TURN @ 8192 TURNS, PROFIBUS  | 1   |
| FILTER, OIL, 3-1/2 IN DIA X 16 IN LG, ROUND  | 6   |
| FILTER, OIL, 3-1/2 IN DIA X 26 IN LG, ROUND  | 6   |
| FILTER, OIL, 3-1/8 IN DIA X 16 IN LG, ROUND  | 6   |
| FILTER, WATER, ***, 5 IN DIA X 8 IN LG, ROUND, F/ WATER SEPARATOR  | 6   |

| Cat Desc   | Qty |
|--|-----|
| GASKET, ***, 7 IN WD X 10-1/2 IN LG, OBLONG, F/ GEAR CASE  | 1   |
| GASKET, FULL FACE, 3-5/8 IN ID X 6-5/16 IN OD X 1/16 IN THK, 6 HOLES, ROUND  | 1   |
| GEAR, SPUR, ***, 12 TEETH, 2.362 IN PITCH DIA, 4140 ALLOY STEEL, SIZE 5 MOD  | 1   |
| HOLDER, ELECTRICAL BRUSH, ***, KIT, 15AMP DOUBLE R SERIES  | 1   |
| HOLDER, ELECTRICAL BRUSH, ***, KIT, 35AMP SINGLE R SERIES  | 1   |
| HOLDER, ELECTRICAL BRUSH, 2.5 IN BORE, KIT, 400AMP HEAVY DUTY  | 1   |
| HOOK, LOAD RATED, ASSY, 1/4 TON LOAD, W/ BEARING BLOCK & SAFETY CLIP   | 1   |
| INSERT, COUPLING, STAR, PLASTIC, F/ BYPASS PUMP COUPLING   | 1   |
| INSERT, COUPLING, STAR, PLASTIC, F/ MAIN PUMP COUPLING   | 1   |
| INSULATOR, ***, 3.50B, 15AMP   | 1   |
| INSULATOR, ***, 3.50B, 35AMP   | 1   |
| INSULATOR, ***, 3.50B, 75AMP, SPACER   | 1   |
| JOINT, FIBER OPTIC ROTARY, 78MM WD X 158MM LG, SS HSG, 10 CHANNEL, 1310 WAVELENGTH   | 1   |
| KIT, REPAIR, REBUILD, ASSEMBLED SEALS, PLAIN ENCASED   | 1   |
| KIT, REPAIR, REPLACEMENT, ELECTRIC BRAKE, DISC, PLATES & SPRINGS   | 1   |
| KIT, REPAIR, REPLACEMENT, QUICK COUPLERS, (2) MALE, (2) FEMALE, (2) SETS OF DUST COVERS  | 1   |
| KIT, REPAIR, SEAL, 200 X 120 CYLINDER, 7 O-RINGS, 8 FIBER RINGS, 5 TEFLON RINGS, 5 PLASTIC RINGS   | 1   |
| KIT, REPAIR, SEAL, 250 X 160 CYLINDER, 12 O-RINGS, 6 TEFLON RINGS, 8 FIBER RINGS, 5 PLASTIC RINGS  | 1   |
| LEVER, LIMIT, F/ CHAIN HOIST   | 1   |
| MONITOR, VIDEO, LCD COLOR, FLAT PANEL, 12 IN DIAGONAL, 1024 X 768 RESOLUTION, 90-264VAC, 12/24VDC, RESISTIVE TOUCH SCREEN, ALUM BEZEL        | 1   |
| MOTOR, ELECTRIC, AC, 250 HP, 460VAC, 3PH, 60HZ, 285AMP, 1787 RPM, 449T FRAME, TEFC ENCLOSURE, 1.15 SERVICE FACTOR, CONTINUOUS DUTY, INSUL CL | 1   |
| MOTOR, HYDRAULIC, ***, 23.8 GPM INPUT, 22.1 HP OUTPUT, 375 RPM, 3340 PSI CONTINUOUS  | 2   |
| MOTOR, HYDRAULIC, FIXED DISPLACEMENT, 95.6 GPM OUTPUT, 4500 RPM, AXIAL PISTON, 4 BOLT SAE, 4550 PSI CONT                                     | 1   |
| O-RING, ***, 0.375 IN ID, 0.5 IN OD  | 4   |
| O-RING, ***, 13 IN ID, 13.25 IN OD, 0.125 IN WD, 279   | 2   |
| O-RING, ***, 5 IN ID, 5.25 IN OD, 0.125 IN WD, 250   | 1   |
| O-RING, ***, 5 IN ID, 5.25 IN OD, 0.125 IN WD, 8-250   | 1   |
| O-RING, ***, 5.5 IN ID, 5.625 IN OD, 0.125 IN WD   | 1   |
| O-RING, ***, 5.625 IN ID, 5.875 IN OD, 0.125 IN WD, 255  | 1   |
| O-RING, ***, 5.625 IN ID, 5.875 IN OD, 0.125 IN WD, 8-255  | 1   |
| O-RING, ***, 7.75 IN ID, 7.938 IN OD, 0.094 IN WD, 170   | 2   |
| O-RING, ***, 9 IN ID, 9.188 IN OD, 0.094 IN WD, 175  | 2   |
| PIN, BUCKET, 3-1/4 IN DIA X 23-1/2 IN LG, AISI 4340 ALLOY STEEL  | 1   |
| PIN, CYLINDER, 6-1/4 IN DIA X 16-1/4 IN LG, STEEL, ASTM C1026  | 1   |
| PIN, LOCKING, TWIST LOCK F/ GRAB QUICK CHANGER   | 1   |

| Cat Desc   | Qty |
|--|-----|
| PIN, PIVOT, 10 IN ID X 14 IN OD X 78 IN LG, STEEL  | 1   |
| PIN, PIVOT, 9-3/4 IN DIA X 30-1/2 IN LG, STEEL, ASTM C1026   | 1   |
| PIN, PIVOT, 9-3/4 IN DIA X 46 IN LG, STEEL, ASTM C1026   | 1   |
| PIN, PIVOT, 9-3/4 IN DIA X 58 IN LG, STEEL, ASTM C1026   | 1   |
| POWER SUPPLY, AC, 85-132/170-265VAC 47/63HZ  | 1   |
| RELAY, GENERAL PURPOSE, 10AMP, 2 FORM C, (1) SILVER NICKEL CONTACT, DPDT, 24VDC COIL, PIN TERMINAL, SOCKET MOUNT, TRANSPARENT DUST COVER ENC | 4   |
| RING, NILOS, REDUCER, 4-3/4 IN ID X 7 IN OD X 1-1/4 IN WD, METAL   | 1   |
| SEAL, OIL, SINGLE LIP, 130MM ID, 160MM OD, 12MM WD, RUBBER COATED STEEL CAGE   | 2   |
| SEAL, OIL, SINGLE LIP, 60MM ID, 85MM OD, 10MM WD, RUBBER COATED STEEL CAGE   | 1   |
| SPEED REDUCER, PLANETARY GEAR TRIPLE REDUCTION, 63:1 RATIO, 3000 RPM INPUT, BODY MOUNT, STRAIGHT ANGLE, STEEL, 21338 FT-LB TORQUE CAPACITY   | 1   |
| SWITCH, PILOT VALVE, 115V, 40-60HZ   | 1   |
| SWITCH, PUSHBUTTON, ***, 1NC, RED CAP, BOOTLESS, EXT HEAD, NEMA 4, 4X, 13, NON-ILLUMINATED   | 1   |
| SWITCH, PUSHBUTTON, ***, 1NO, GREEN CAP, BOOTLESS, FLUSH HEAD, NEMA 4, 4X, 13, NON-ILLUMINATED   | 2   |
| SWITCH, PUSHBUTTON, 600VAC 10AMP, 2NCLB, RED, 30.5MM HOLE MOUNT, 2-POSITION, PUSH-PULL, NON-ILLUMINATED                                      | 1   |
| SWITCH, SELECTOR, ***, 1NO-1NC, 3 MAINTAINED POSITION, STANDARD KNOB OPERATED, BLACK, NEMA 4, 4X, 13   | 1   |
| TRANSMITTER, PRESSURE, 0-350 BAR INPUT, 4-20MA OUTPUT, 12-30VDC SUPPLY, 1/4 IN MNPT, SS, A08 HIGH PRESSURE, SENSOR                           | 2   |
| TUBE, BRUSH EXTRUDE, 3/4 IN SQ X 3 FT LG, PVC  | 3   |
| VALVE, PROPORTIONAL, 20 BAR, PILOT OPERATED, F/ HYDRAULIC CONTROLS   | 1   |
| VALVE, PROPORTIONAL, 24V 8AMP, PILOT OPERATED  | 2   |
| VALVE, PROPORTIONAL, 24VDC, PILOT OPERATED, 20 BAR   | 1   |
| WASHER, THRUST, 10 IN ID, 14 IN OD, .62 IN THK, OIL LITE BRASS, RPM DWG MET 21904  | 1   |
| WASHER, THRUST, 14-1/2 IN ID, 18-1/2 IN OD, .62 IN THK, OIL LITE BRASS, RPM DWG MET 21903  | 1   |
| WRENCH SET, COMBINATION & HEX KEY, 7 COMBO & 15 HEX KEYS, CONSISTS OF:   |     |