

| Etrali Parts (Spare V23.35 Sytem 4th Floor Transmission Operartions) | |
|---|---|
| s/n 042199 | |
| | |
| Quantity | Description |
| 1 | Assembled Etrali Cabinet 23"W x 26"D x 82"H, wired for 24 - 2MB Turret Positions 192 - Analog Input Channels none - T1 or ISDN T1 Network Lines 6 - 30 Channel Recording via 2MB Interface NIPC dual network to Admin PC (NIPC-5.07 rev 23.20) 48 Volt DC Power |
| 2 | SIM509, Kernel Version 23.35., System Processor Cards |
| 2 | SIM630, Kernel Interface Cards |
| 1 | SIM034-4, System Tone Card |
| 2 | CSY SIM406, TDM Bus Synchronization Cards |
| 8 | 2048 IT DIB, TDM Shelf Double Bus Interface Cards |
| 9 | SIM624-1, DC Shelf Power Supply Cards |
| 2 | SIM719, 12-Turret Position Shelf Processor Card |
| 12 | SIM604, Dual Turret Position Interface Card, 2MB link |
| 3 | SIM410, Analog Shelf Slow Bus Interface Card |
| 36 | SIM207, 4-Analog Input Line Cards |
| 1 | SIM719, 30-Channel Recording Interface Card, 2MB Link |
| | |
| 18 | Mach-2 Turrets |
| | |

| Etrali Parts (Spare V22.70 Sytem 5th Floor Telecom Room) | |
|---|--|
| | s/n 092402 |
| | |
| Quantity | Description |
| 1 | Assembled Etrali Cabinet 23"W x 26"D x 82"H, wired for 60 - 2MB Turret Positions 64 - Analog Input Channels 2 - T1 or ISDN T1 Network Lines 6 - 30 Channel Recording via 2MB Interface 2 - IP Ethernet Lan for Admin PC (NIPC-4.39 rev 22.50) 48 Volt DC Power |
| 2 | SIM709, Kernel Version 22.70, System Processor Cards |
| 2 | SIM730, Kernel Interface Cards |
| 1 | SIM034-4, System Tone Card |
| 2 | CSY SIM606, TDM Bus Synchronization Cards |
| 10 | 2048 IT DIB, TDM Shelf Double Bus Interface Cards |
| 8 | SIM624-1, DC Shelf Power Supply Cards |
| 1 | SIM719, 12-Turret Position Shelf Processor Card |
| 14 | SIM604, Dual Turret Position Interface Card, 2MB link |
| 1 | SIM410, Analog Shelf Slow Bus Interface Card |
| 4 | SIM207, 4-Analog Input Line Cards |
| 1 | SIM719, Dual ISDN-T1 Shelf Processor Card |
| 1 | SIM244, Dual ISDN-T1 Shelf Interface Card |
| 2 | SIM441, T1 Network Interface Card |
| 1 | SIM719, 30-Channel Recording Interface Card, 2MB Link |
| | |
| 4 | Mach-2 Turrets |

| Nice Spare Parts | |
|-------------------------|--|
| Quantity | Description |
| 1 | NiceLog, software version 7.61, DOS based. |
| | <i>Single sytem with logger & server</i> |
| | 256 hours of active message retention |
| | Single DAT-2 (4GB) tape drive. Configurable between archiving and retrieval. |
| | Client access through ethernet LAN board. |
| | 30 channels, composed of one Etrali 2MB link. |
| | 4 analog output channels |
| | 2 telephone dial up analog output bridge ports. |
| | |
| | |
| 1 | NiceLog & CLS, software version 8.70, Windows NT4.0 based. |
| | <i>one logger & one CLS server</i> |
| | 4324 hours of active message retention |
| | Dual DAT-3 (24GB) tape drives. Configurable for both archiving and retrieval. |
| | Client access through ethernet LAN board. |
| | Client access groups capable. |
| | 60 channels, composed of two Etrali 2MB links. |
| | CLS server provides logger access, Etrali key card to agent mapping, dialed digits, and other caller ID information. |
| | 4 analog output channels |
| | 2 telephone dial up analog output bridge ports. |
| | |
| | |
| | |