

December 19, 2013

Product Specification Sheet



Product: TRPX 750-58 FCCU 220 NL-EPR TS CPE JKT 15KV

Cdr. Strand: 750-58 X .1219 Full Compact Nominal Diameter: .908"

Strand Shield: Nominal Wall .026" Nominal Diameter: .959"

Insulation: Nat. EPR .220" Wall Nominal Diameter: 1.410"

Insulation Shield: Nominal Wall .042" Nominal Diameter: 1.495"

Tape Shield: .005" Thick Copper Tape Nominal Diameter: 1.515"

CPE Jacket: Minimum Wall .100" Nominal Diameter: 1.725"

Sample Print: SOUTHWIRE POWER CABLE EXXXX (UL) 750KCMIL COMPACT
 CU 220 MIL NL-EPR CPE JKT 15KV TYPE MV105 133% INS LEVEL
 25% TS FOR CT USE SUN RES OIL RES I/II YEAR PHASE (A) (B) (C)

Cable: Three conductors cable together
 With a nominal 103" LH Lay Nominal Diameter: 3.760"

Cable Wt. Nominal: 10075 lbs./M Ft.
 Standards UL 1072

* All Dimensions and weights are to be considered nominal and subject to normal manufacturing variations. Drawing for reference only and not to scale.