

# Uniblend®

EPR/Copper Tape Shield/PVC, Medium-Voltage Power, Shielded  
15kV, UL Type MV-105, 133% Ins. Level, 220 Mils



### Features:

- Rated at 105°C
- Excellent heat and moisture resistance
- Excellent flame resistance
- Outstanding corona resistance
- Flexibility for easy handling
- High dielectric strength
- Low moisture absorption
- Electrical stability under stress
- Low dielectric loss
- Chemical-resistant
- Meets cold bend test at -35°C

### Compliances:

- National Electrical Code (NEC)
- UL 1072
- ICEA S-93-639/NEMA WC74
- ICEA S-97-682
- AIEC CS8
- UL listed as Type MV-105 for use in accordance with NEC, UL File # E90501
- UL 1685 (Sizes 1/0 AWG and larger) UL Flame Exposure Test
- Sizes 1/0 AWG and larger are listed and marked "Sunlight-Resistant FOR CT USE" in accordance with NEC
- IEEE 1202 (70,000 BTU/hr)/CSA FT4
- EPA 40 CFR, Part 261 for leachable lead content per TCLP method
- OSHA Acceptable
- Optional Flame Tests:**
- ICEA T-29-520 (210,000 BTU/hr)

### Packaging:

- Material cut to length and shipped on non-returnable wood reels. Lengths in excess of 10,000 lbs. are provided on returnable steel reels that require a deposit
- Extra charges apply for cuts less than 1000 ft., lagging, pulling eyes, paralleling and triplexing

### Product Construction:

#### Conductor:

- 2 AWG thru 1000 kcmil annealed bare copper compact Class B strand

#### Extruded Strand Shield (ESS):

- Extruded thermoset semi-conducting stress-control layer over conductor

#### Insulation:

- Ethylene Propylene Rubber (EPR) insulation, colored to contrast with the black conducting shield layers

#### Extruded Insulation Shield (EIS):

- Thermoset semi-conducting polymeric layer free stripping from insulation

#### Metallic Shield:

- 5 mil annealed copper tape with an overlap of 25%

#### Jacket:

- Lead-free, flame-retardant, moisture- and sunlight-resistant Polyvinyl Chloride (PVC)

#### Print:

- GENERAL CABLE® (PLANT OF MFG) (MO/YR OF MANUFACTURE) LIGHTNING BOLT SYMBOL 1/C SIZE (AWG OR KCMIL) COMPACT CU UNIBLEND® PVC JKT (INSULATION THICKNESS)

### Print (cont'd.):

EPR TYPE MV-105 (VOLTAGE) KV% INSULATION LEVEL SUN RES FOR CT USE (UL) SEQUENTIAL FOOTAGE MARK

\* Sizes smaller than 1/0 AWG do not include "FOR CT USE".

### Options:

- PVC jacket colors other than black
- Flame-retardant Chlorinated Polyethylene (CPE) jacket
- Low-Smoke, Zero-Halogen (LSZH) jacket
- STRANDFILL® – blocked conductor. Tested in accordance with ICEA T-31-610
- 100% insulation level

### Applications:

- Superior performance in petrochemical plants, pulp and paper mills, sewage and water treatment plants, environmental protection systems, railroads, mines, utility power generating stations, steel mills, textile plants and other industrial three-phase applications
- For use in wet or dry locations when installed in accordance with NEC
- For use in aerial, conduit, open tray and underground duct installations
- For use in direct burial if installed in a system with a ground conductor that is in close proximity, and conforms with NEC 250.4 (A) (5)

CATALOG NUMBER	COND. SIZE (AWG/kcmil)	NOMINAL CONDUCTOR DIAMETER INCHES	INSULATION DIAMETER INCHES		NOMINAL JACKET THICKNESS		NOMINAL CABLE				COPPER WEIGHT		AMPACITY			CONDUIT SIZING (4) (INCHES)
			MIN.	MAX.	INCHES	mm	INCHES	mm	INCHES	mm	LBS/1000 FT	kg/km	LBS/1000 FT	kg/km	CONDUIT IN AIR (1)	
<b>15kV<sup>‡</sup>, UL TYPE MV-105, 133% INS. LEVEL, 220 MILS</b>																
17031.130200	2	0.27	0.710	0.800	0.080	2.03	0.99	25.14	658	979	276	411	165	165	-	3
17031.130100*	1	0.31	0.745	0.830	0.080	2.03	1.02	25.91	733	1090	332	494	190	185	-	3.5
17031.135100	1/0	0.34	0.780	0.865	0.080	2.03	1.06	26.92	825	1228	403	600	215	215	220	3.5
17031.135200	2/0	0.38	0.820	0.905	0.080	2.03	1.10	27.94	938	1396	492	732	255	245	250	3.5
17031.135300*	3/0	0.43	0.865	0.955	0.080	2.03	1.14	28.95	1078	1604	603	897	290	275	290	3.5
17031.135400	4/0	0.48	0.920	1.005	0.080	2.03	1.21	30.73	1261	1876	743	1105	330	315	335	3.5
17031.136000	250	0.53	0.970	1.060	0.080	2.03	1.25	31.75	1407	2093	866	1289	365	345	370	4
17031.136200	350	0.62	1.070	1.155	0.080	2.03	1.35	34.29	1783	2653	1184	1761	440	415	460	5
17031.136500	500	0.74	1.190	1.275	0.080	2.03	1.47	37.34	2331	3468	1657	2466	535	500	575	5
17031.137000	750	0.91	1.370	1.460	0.080	2.03	1.65	41.91	3234	4812	2445	3638	655	610	745	6
17031.137500	1000	1.06	1.520	1.610	0.110	2.79	1.86	47.24	4219	6278	3228	4803	755	690	890	6

Dimensions and weights are nominal; subject to industry tolerances.

\* Non-stock item; minimum runs apply. Please consult Customer Service for price and delivery.

(1) Ampacities are in accordance with Table 310-73 of the NEC for triplexed or three single conductor copper cable in isolated conduit in air, based on a conductor temperature of 105°C (221°F) and an ambient air temperature of 40°C (104°F).

(2) Ampacities are in accordance with Table 310-77 of the NEC for triplexed or three single conductor copper cable in underground ducts (three conductors per duct), based on a conductor temperature of 105°C (221°F) and an ambient earth temperature of 20°C (68°F), electrical duct arrangement per Figure 310.60 Detail 1, 100% load factor, and earth thermal resistance (rho) of 90.

(3) Ampacities are based on single conductor Type MV-105 sizes #1/0 AWG and larger in an uncovered tray in accordance with Section 392-13(B) of the NEC at an ambient air temperature of 40°C (104°F); the ampacities are based on 75% of the values per Table 310-69. For cable trays with unventilated covers for more than 6 feet, the ampacities shall not exceed 95% of the values shown above.

(4) Based on nominal cable diameters, three single cables in the duct (PVC Schedule 40) with no ground wire and a maximum of 40% fill. Jam ratio has been considered, but it should be checked for individual installations.

‡100% insulation level is available upon request

Note: a) Sizes smaller than 1/0 AWG do not include "FOR CT USE".

b) The NESC Lightning bolt symbol is on all Uniblend® constructions.



Phone: 888-593-3355  
www.generalcable.com